

513.738.3311 www.myronbowling.com

SANTEE COOPER

TUESDAY, MAY 4, AT 10AM ET WEBCAST ONLY - NO ON-SITE BIDDING

EQUIPMENT LOCATION:

553 Cross Station Rd., Pineville, SC 29468

ON-SITE CONTACT:

REMOVAL HOURS:

Monday – Friday: 8:00AM - 5:00PM

All purchases must be removed by **THURSDAY**, 6/1/23

18% BUYER'S PREMIUM IN EFFECT FOR THIS AUCTION

Click Here to register for the auction and view the lot list on Bidspotter

Although information has been obtained from sources deemed reliable, the auctioneer makes no warranty or guarantee expressed or implied, as to the accuracy of the information herein contained. It is for this reason that buyers should avail themselves of the opportunity to make inspection prior to the sale.

Complete terms of sale can be found on our website

All equipment is sold "as is", "where is", and all sales are final.

Myron Bowling Auctioneers, Inc. makes no warranties, either expressed or implied, as to the condition of any item.

The Purchaser takes full responsibility for any item purchased at the time it is sold.

Unless cash, certified funds or cashiers checks are used for payment, titles will be mailed to you or your bank as soon as funds issued have cleared your bank.

Myron Bowling Auctioneers, Inc. does not do rigging or assist in any way in the rigging process. You may contract with a rigging service or perform the removal yourself. In either case, a Certificate of Insurance must be presented in the correct amount before entering the property.

Refunds, if any, are at the discretion of the Auctioneer.

The term "times the money" means we are selling a lot with multiple items. As an example, 5 electric drills: (if you bid \$100, you will pay \$100 x 5 or \$500).

> www.myronbowling.com OFFICE: (513) 738-3311

| Lot Number | Description |
|---------------|--|
| 1 | GE Generator Stator Housing for 615 MW Electric Super Critical Steam Turbine, Hydrogen & Water Cooled, 2 Poles, 3 Phase WYE Conn. 60 HZ, Gas Pressure 98% H2 60 PSIG, Kva: 750,000, Armature Amps: 20,620, Armature Volts: 21,000, Field Amps: 3,998, Excitation Volts: 605, Power Factor: 0.9, & LPA Rotor from a 615 MW GE Steam Turbine, 22-Stage, 3,600 RPM, Super Critical Steam Condition Pressure: 3,515 PSIA, Temperature: 1,050 Deg. F., Exhaust Pressure: 3.45" HGA, Approx. Weight: 65,000+ LB. |